


LED T8 Weatherproof Fixture




- Adjustable surface mounted LED weatherproof
- Clear / frosted tempered glass
- Aluminium housing
- 0-10V / TRIAC / DALI dimmable version available



Size (mm)	Model	Wattage	Lumen	CCT	CRI	Input voltage	PF
670x90x90	WPM061	1x 10W	1300lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1230x90x90	WPM121	1x 18W	2340lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1530x90x90	WPM151	1x 23W	3000lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
670x125x90	WPM062	2x 10W	2x 1300lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1230x125x90	WPM122	2x 18W	2x 2340lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1530x125x90	WPM152	2x 23W	2x 3000lm	3000K/4000K/6500K	>80	AC100-240V	>0.9

LED T5 Weatherproof Fixture



- Adjustable surface mounted LED weatherproof
- Clear / frosted tempered glass
- Aluminium housing
- 0-10V / TRIAC / DALI dimmable version available



Size (mm)	Model	Wattage	Lumen	CCT	CRI	Input voltage	PF
630x90x90	WPM061-T5	1x 10W	1300lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1230x90x90	WPM121-T5	1x 16W	2300lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1530x90x90	WPM151-T5	1x 23W	3450lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
630x125x90	WPM062-T5	2x 10W	2x 1300lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1230x125x90	WPM122-T5	2x 16W	2x 2300lm	3000K/4000K/6500K	>80	AC100-240V	>0.9
1530x125x90	WPM152-T5	2x 23W	2x 3450lm	3000K/4000K/6500K	>80	AC100-240V	>0.9