




Specification

- High lumen efficiency COB
- IP20/IP44 protection grade available
- High quality aluminium heat sink
- External constant current LED driver
- DALI/0-10V/TRIAC dimmable available




Cut-out	Dimension	Model	Wattage	Lumen	CCT	CRI	Input voltage
90mm	Φ110 x 60	BDLBC306	6W	540-570lm	3000K/4000K/5000K	>80 / >90	AC100-240V
90mm	Φ110 x 60	BDLBC309	9W	810-855lm	3000K/4000K/5000K	>80 / >90	AC100-240V
125mm	Φ155 x 84	BDLBC406	6W	540-570lm	3000K/4000K/5000K	>80 / >90	AC100-240V
125mm	Φ155 x 84	BDLBC409	9W	810-855lm	3000K/4000K/5000K	>80 / >90	AC100-240V
125mm	Φ155 x 84	BDLBC412	12W	1080-1140lm	3000K/4000K/5000K	>80 / >90	AC100-240V
145mm	Φ175 x 85	BDLBC512	12W	1080-1140lm	3000K/4000K/5000K	>80 / >90	AC100-240V
145mm	Φ175 x 85	BDLBC520	20W	1800-1900lm	3000K/4000K/5000K	>80 / >90	AC100-240V
145mm	Φ175 x 85	BDLBC524	24W	2100-2280lm	3000K/4000K/5000K	>80 / >90	AC100-240V



Specification

- High lumen efficiency COB
- IP20/IP44 protection grade available
- High quality aluminium heat sink
- External constant current LED driver
- DALI/0-10V/TRIAC dimmable available



Cut-out	Dimension	Model	Wattage	Lumen	CCT	CRI	Input voltage
165mm	Φ195 x 86	BDLBC612	12W	1080-1140lm	3000K/4000K/5000K	>80 / >90	AC100-240V
165mm	Φ195 x 86	BDLBC620	20W	1800-1900lm	3000K/4000K/5000K	>80 / >90	AC100-240V
165mm	Φ195 x 86	BDLBC624	24W	2160-2280lm	3000K/4000K/5000K	>80 / >90	AC100-240V
165mm	Φ195 x 86	BDLBC630	30W	2700-2850lm	3000K/4000K/5000K	>80 / >90	AC100-240V
165mm	Φ195 x 86	BDLBC636	36W	3240-3420lm	3000K/4000K/5000K	>80 / >90	AC100-240V
210mm	Φ245 x 100	BDLBC824	24W	2160-2280lm	3000K/4000K/5000K	>80 / >90	AC100-240V
210mm	Φ245 x 100	BDLBC830	30W	2700-2850lm	3000K/4000K/5000K	>80 / >90	AC100-240V
210mm	Φ245 x 100	BDLBC836	36W	3240-3420lm	3000K/4000K/5000K	>80 / >90	AC100-240V
210mm	Φ245 x 100	BDLBC842	42W	3780-3990lm	3000K/4000K/5000K	>80 / >90	AC100-240V
210mm	Φ245 x 100	BDLBC848	48W	4320-4560lm	3000K/4000K/5000K	>80 / >90	AC100-240V