




Specification

- High lumen efficiency SMD
- IP20/IP44 protection grade available
- Aluminium housing
- High transmittance PC
- External constant current LED driver
- DALI/0-10V/TRIAC dimmable available




Cut-out	Dimension	Model	Wattage	Lumen	CCT	CRI	Input voltage
90mm	Φ110 x 40	BDLBS306	6W	540-600lm	3000K/4000K/6500K	>80 / >90	AC100-240V
90mm	Φ110 x 40	BDLBS309	9W	810-900lm	3000K/4000K/6500K	>80 / >90	AC100-240V
125mm	Φ155 x 54	BDLBS406	6W	540-600lm	3000K/4000K/6500K	>80 / >90	AC100-240V
125mm	Φ155 x 54	BDLBS409	9W	810-900lm	3000K/4000K/6500K	>80 / >90	AC100-240V
125mm	Φ155 x 54	BDLBS412	12W	1080-1200lm	3000K/4000K/6500K	>80 / >90	AC100-240V
145mm	Φ175 x 55	BDLBS512	12W	1080-1200lm	3000K/4000K/6500K	>80 / >90	AC100-240V
145mm	Φ175 x 55	BDLBS515	15W	1350-1500lm	3000K/4000K/6500K	>80 / >90	AC100-240V
145mm	Φ175 x 55	BDLBS520	20W	1800-2000lm	3000K/4000K/6500K	>80 / >90	AC100-240V
145mm	Φ175 x 55	BDLBS524	24W	2160-2400lm	3000K/4000K/6500K	>80 / >90	AC100-240V



Specification

- High lumen efficiency SMD
- IP20/IP44 protection grade available
- Aluminium housing
- High transmittance PC
- External constant current LED driver
- DALI/0-10V/TRIAC dimmable available



Cut-out	Dimension	Model	Wattage	Lumen	CCT	CRI	Input voltage
165mm	Φ195 x 56	BDLBS612	12W	1080-1200lm	3000K/4000K/6500K	>80 / >90	AC100-240V
165mm	Φ195 x 56	BDLBS615	15W	1350-1500lm	3000K/4000K/6500K	>80 / >90	AC100-240V
165mm	Φ195 x 56	BDLBS620	20W	1800-2000lm	3000K/4000K/6500K	>80 / >90	AC100-240V
165mm	Φ195 x 56	BDLBS624	24W	2160-2400lm	3000K/4000K/6500K	>80 / >90	AC100-240V
165mm	Φ195 x 56	BDLBS630	30W	3150-3300lm	3000K/4000K/6500K	>80 / >90	AC100-240V
165mm	Φ195 x 56	BDLBS636	36W	3780-3960lm	3000K/4000K/6500K	>80 / >90	AC100-240V
210mm	Φ245 x 54	BDLBS824	24W	2160-2400lm	3000K/4000K/6500K	>80 / >90	AC100-240V
210mm	Φ245 x 54	BDLBS830	30W	3150-3300lm	3000K/4000K/6500K	>80 / >90	AC100-240V
210mm	Φ245 x 54	BDLBS836	36W	3780-3960lm	3000K/4000K/6500K	>80 / >90	AC100-240V
210mm	Φ245 x 54	BDLBS842	42W	4410-4620lm	3000K/4000K/6500K	>80 / >90	AC100-240V
210mm	Φ245 x 54	BDLBS848	48W	5040-5280lm	3000K/4000K/6500K	>80 / >90	AC100-240V