



Matt silver



Glossy silver




Black



Golden

Specification

- High lumen efficiency COB
- IP20/IP44 protection grade available
- Aluminium housing
- External constant LED driver
- DALI/0-10V/TRIAC dimmable available



Cut-out	Dimension	Model	Wattage	Lumen	CCT	CRI	Input voltage
90mm	Φ100 x 75	DL092709	9W	720lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
90mm	Φ100 x 75	DL092712	12W	960lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
100mm	Φ110 x 80	DL092715	15W	1200lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
100mm	Φ110 x 80	DL092720	20W	1600lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
125mm	Φ135 x 96	DL092720-2	20W	1600lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
125mm	Φ135 x 96	DL092730	30W	2500lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
150mm	Φ170 x 112	DL092730-2	30W	2500lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
150mm	Φ170 x 112	DL092740	40W	3400lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
200mm	Φ215 x 135	DL092740-2	40W	3400lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V
200mm	Φ215 x 135	DL092750	50W	4200lm	2700K/3000K/4000K/5000K/6000K	>80 / >90	AC100-240V