

Flood Light Series



40W, 60W, 80W



100W, 120W, 150W



180W, 200W, 240W



Specification

- OSRAM LED, high lumen efficiency
- Beam angle : 15° / 30° / 30x60° / 65x120°
- Die-casting aluminium housing
- High strength toughened glass
- Built-in 10kV surge protection device



Model	Wattage	Size(mm)	Lumen	CCT	CRI	Input voltage	PF
FLH040	40W	L308 x W359 x H88	4800lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH060	60W	L308 x W359 x H88	7200lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH080	80W	L308 x W359 x H88	9600lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH100	100W	L366 x W413 x H83	12000lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH120	120W	L366 x W413 x H83	14400lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH150	150W	L366 x W413 x H83	18000lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH180	180W	L462 x W452 x H88	21600lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH200	200W	L462 x W452 x H88	24000lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9
FLH240	240W	L462 x W452 x H88	26400lm	3000K/4000K/5000K	73/80	AC100-277V	>0.9